

Banding Tools

Product Description/ Specification

Standard Banding Tool is used to fix stainless steel banding and strapping through to the operation to tighten. This is ideal for various applications of banding including Bandfix® Sign Banding, often used with a sign to band it to a post similarly with bins often used by councils to secure the bin to a post. These can also be used for cables, metal insulation, packing etc. with our Bandfix® Value band or heavier insulation products. These are regularly used on industrial Oil and Gas Pipeline Insulation by metal ladders to hold metal securely around pipework or tanks. The tools tensions over 1100 kg (2,400 lbs) and cuts off the spare banding.

BS Stainless do 3 different designs of these tools:

- Standard Banding Tool, Giant Banding Tool—These are also referred to as a "Whirley Bird" bander
- Tensioner Banding Tool

Tools are used to apply stainless steel bandings, but can also be used with Galvanised or carbon steel banding and general steel strapping.

Designs and Specification



Standard Tool

Light Weight Application

Widths—9mm (3/8") to 20mm (3/4")

Weight 2kgs approx. (4.3lb)

Heat treated tool with built in cutter

Spring loaded grip lever for ease of use

Corrosion resistant blue epoxy coating



Giant Banding Tool

High Tension Wide Bands

Widths—19mm (3/4") to 32mm (1¼")

Weight 5kgs approx. (12.3lb)

Heat treated tool with built in cutter

Spring loaded grip lever for ease of use

Corrosion resistant epoxy coating



Tensioner Banding tool

High Tension wider Bands

Widths—9mm (3/8") to 20mm (3/4")

Weight 2kgs approx. (4.3 lb.)

Includes cutter and hammer

Maximum Thickness 0.03" (0.76mm)

Epoxy coated handles for good grip

For full details on application, please refer to BS Stainless 'Banding Tool Instructions'



2731 ISO 9001: 2008



BS Stainless Limited—360 Leach Place, Walton Summit, Preston, PR5 8AS T: +44 (0) 1772 337555 F: +44 (0) 1772 313010 E: info@bsstainless.com

www.bsstainless.com