


## **MATERIAL DATA SHEET**

CoolMet<sup>®</sup> Insulation Jacketing is a metal jacket painted on the topside. CoolMet uses an innovative PVDF (Poly Vinylidine Fluoride) paint system which focuses on improvement of 2 most important thermal properties, Emissivity and Reflectance to ensure maximum heat radiation away from the surface resulting in lower surface temperature. Along with excellent radiative properties, CoolMet also exhibits exceptional weather resistance. High abrasion and corrosion resistance along with high resistance to chemical attack, makes this the best choice as a metal jacket. Especially effective in applications such as oil and gas processing and transportation, petrochemical plants, power stations and for any jacketing applications in highly corrosive environments.



CoolMet is also available with a range of options for the underside of the jacketing:

- Polyester paint or other paint systems based on the specification
- M DryMet moisture barrier to prevent galvanic corrosion of the jacketing
- SoundMet acoustic insulation for effective noise insulation

Standard CoolMet is produced in grey, other colours are available on requested. Most common base metals are Stainless Steel and Aluminium, other metals are available as per project specification. Corrugated, embossed and other profiles are also available in CoolMet.

PROPERTY	SPECIFICATION	PERFORMANCE
Emissivity	ASTM E 1933 99A	0.9>
Resistance to Cracking (T - Bend)	EN 13523 - 7	1.0T on HDG Without Removal
Resistance to Solvent (MEK)	EN 13523 - 11	150 double rubs
Scratch Resistance	ISO 1518:2000	2.9 kg
Weathering, colour retention	ASTM D 2244	4 years 45 degrees subtropical exposure 45 Degrees
Weathering, chalk resistance	ASTM D 4214	4 years 45 degrees subtropical exposure 45 Degrees
Salt Spray Test	ASTM B 117	1000 hrs 0-5 creep
Humidity	ASTM D 2247	0-1 cut edge creep (1000 hrs)

## Safety:

There are no known health risks in handling CoolMet. For more details on safety, please refer to CoolMet MSDS available on our website.







BS Stainless Limited - 360 Leach Place, Walton Summit, Preston, PR5 8AS Tel: +44 (0) 1772 337555 | +44 (0) 1772 313010 | Email: info@bsstainless.com www.bsstainless.com