
Aluminium Eco Seal

Product Description/ Specification:

Wing seals are used to secure the metal banding around the cladding or insulation materials after applying appropriate tension in the bands. These are manufactured from Aluminium.

Design:

Standard seals are pressed from Aluminium banding in either 0.5mm or 0.7mm thickness. Unless specified at the time of the order, BS Stainless reserves the right to supply either thicknesses based on the availability. Most common widths are ½" (13mm) and ¾" (19mm).

Other sizes available: 5/8" (16mm), 1" (25mm), 1 1/2" (40mm) and 2" (50mm)

Wing Seals can also be available in other thicknesses if requested.

BS Stainless have also developed Eco seals, which are innovative design wing seals. These wing seals allow a reduction on the material thickness but still achieves a significant improvement in the strength.


These wing seals are only available on request. Unless specified at the time of the order, we will supply standard wing seals

Safety:


There are no known health risks in handling Aluminium, although it is recommended that gloves should be worn in case of sharp edges. Good lifting practice techniques should always be followed when handling these products.

Packaging:

Seals are packed in either boxes of 1000 or sacks of 5000, although these can be adapted for special requirements. Material will be packed on wooden pallets approximately 1000mm X 1200mm and shrink wrapped. Heat treated pallets will be supplied if requested.



Standard Wing Seal



Eco Seal