

Stainless Steel Banding

Product Description/ Specification:

Austenitic Stainless Steel ASTM A240/ ASTM A167/ EN 10088-4.

Metal Banding are used as fixing system in insulation and sign industry. BS Stainless specialise in the supply of high performance banding for all applications. Banding are manufactured in the UK to Construction Products Regulation (CPR 305/2011) CE marking standard, within the scope of ISO 9001:2008 management system . Relevant CE and ISO certificates are available on our website.

Popular grades we supply are 304/304L, 316/316L, other grades are available to order.

Dimensions:

Standard Widths of Banding Supplied are:

1/2" (13mm), 5/8" (16mm), 3/4" (19mm), 1" (25mm) - Other sizes available

Most Common thickness—0.4mm & 0.5mm, different thicknesses can be produced as per requirement

Tolerance:

Thickness +/- 0.05mm and Width +/- 1 mm

Painted Banding:

We also supply painted banding with high performance paints for identification, aesthetic applications or even corrosion prevention. Banding can be produced in any colour based on customer requirement, most popular colours available are blue and black. For more details, please refer to painted banding datasheet.

Packaging:

All coils are in catch weight suitable for lifting by hand, typical weights are 15—20 Kgs with a standard lifting slit edge. Alternatively, ribbon wound edge dressed bandings can be supplied packed in cardboard boxes. We also supply coils oscillat-ed wound. Individual coil weights are flexible to suit customer requirements.

Materials will be shipped on wooden pallets approximately 1000mm X 1200mm X 500mm and shrink wrapped. Heat treated pallets will be supplied where requested.

Finish:

The finish will not affect the properties or application of the materials, it is completely visual. The material finish for banding can be either a 2B (matt finish) or a BA (bright finish). Unless specified, the material shipped can be either finish or both.

