

360 Leach Place Walton Summit Bamber Bridge Preston PRS 8AS P: 01772 337555 F: 01772 301031 E: info@bsstainless.co.uk

BS Purchasing Specification – 001

Issue I

1. Purpose:

- 1.1. To ensure the procedures and services obtained from the suppliers are capable of meeting Company quality requirements.
- 1.2. To ensure suppliers are clearly informed of Company purchase requirements.

2. Scope:

2.1. The specification covers the requirements to be met by suppliers of Stainless Steel strip/coil.

3. Material Specification:

- 3.1. The material shall be supplied in accordance with the formal order sheet, this specification and the relevant material specification in that priority.
- 3.2. The material must be in accordance with the following standards:

BS EN 10088-4:

Technical delivery conditions for sheet/plate and strip of corrosion resisting steels for construction purposes

ASTM 240/A240M-12:

Standard Specification for Chromium and Chromium-Nickel Stainless Steel Plate, Sheet, and Strip for Pressure Vessels and for General Applications

- 3.3. Strips to be free from bends, creases, twists or nicks that would increase the effective thickness of the coil.
- 3.4. Material to be adequately protected from damage and from the elements in transit.
- 3.5. All coils to be wrapped to keep clean and prevent contamination.

4. Packaging:

- 4.1. Goods are to be adequately protected from damage and from the elements in transit.
- 4.2. All coils must be identified with coil number, supplier name, material thickness, width and weight.
- 4.3. Coil to be 'eye' to sky if on a pallet
- 4.4. Each coil to be separated by a spacer

5. Inspection Checklist:

5.1. Material test certificates must be provided or made accessible to BS Stainless Limited

All coils

Purchase order number

Cast Number/ Traceability

Certificate of Conformity

General / Surface condition

Check 1 coil in each batch

Material thickness outside – Micrometer/ Vernier Coil width – Steel rule

Weight

6. Changes:

6.1. Any proposed changes in the material quality and quality management system must be notified before implementation.